

**PLIDCO® CLAMP+SLEEVE****Couples Pipe, Seals Leaks, & Reinforces Damaged Pipe**

PLIDCO® Clamp+Sleeve grips the outside wall of a pipe to counteract extraordinary end-pull and unusual axial stresses often encountered in off-shore installations. PLIDCO® Clamp+Sleeves provide exceptional holding power minimizing the danger of caving in damaged pipe.

Steel GirderRings hold the packing securely in place during installation, assuring a gas tight, liquid tight seal. PLIDCO® Clamp+Sleeves are available as either an offshore or on-shore package in any size, length, and working pressure. They can be designed for welding or non-welding applications. The sleeve can be reconditioned and used again if not welded. The Plidco® Clamp+Sleeve is designed to ASME code section VIII and meets the intent of API 6H/6X.

Viton packing is standard.

Buna-N, Silicone and other packings are available upon request.

**Standard body materials:**

- SA-516 Gr 70
- SA-350 LF2 Cl1
- SA-352-LCC
- Standard bolting is SA-193 Gr. B7 with SA-194 Gr. 2H nuts

**Options:**

- Marine epoxy paint for corrosion protection
- Hinges for ease of installation and handling
- Vents per customer specifications
- Anodes for cathodic protection
- NACE MR0175 / ISO 15156 compliant materials
- ASME 31.3

